



Flexsteel® 250 CB-20 Steam Hose

APPLICATION:

Flexsteel® 250 CB-20 improves protection for workers handling hose with its enhanced working pressure to burst ratio (20 to 1) and by reducing leaks and dangerous electrostatic charge when used with a crimped fitting. Additionally, the security of a crimped fitting solution can save as much as \$6,200 per coupling every steam season.*



CONSTRUCTION:

TUBE: Chlorobutyl blended synthetic rubber

COVER: Red Pyrosyn® wrapped finish, pin-pricked

REINFORCEMENT: (2) Braided steel wire

TEMPERATURE: 0°F to 425°F (-18°C to 218°C)

PACKAGING:

Reels, cut lengths, coupled assemblies

BRANDING:

Continuous brand example: Goodyear Flexsteel 250 CB-20 Steam 250 psi WP Drain after using.
Made in U.S.A.

COUPLINGS: MxM, MxF, MxMS, FxF, FxMS.

NON-STOCK/SIZES: Contact your Goodyear Engineered Products representative for special production run minimum requirements

SF-SMOOTH FINISH (PIN PRICKED)

ORDER CODES: 3/4 inch: 539-580-024 (red)



ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	in.	lb./ft.	code
3/4	19.1	1-1/4	31.75	250	1.72	0.59	0.88

* Based on an approximate steam loss of 2.6lbs/min @ \$11/1000lbs. steam over a 5 month period. Figures courtesy of CampbellFittings.com.

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2008 Veyance Technologies, Inc. All Rights Reserved.